

Ser. No. 10/619,294, First Response

IN THE CLAIMS

1. (currently amended): A loudspeaker for outputting sound in a frequency range including a lowest frequency f , the lowest frequency f having a wave number k ; the loudspeaker comprising:
a generally arcuate source of wind pulsating at the frequency f , the source having an arcuate radius r such that a quantity rk is approximately equal to or larger than one;

wherein r is greater than 1.00 feet;

whereby wind is converted into sound at the lowest frequency f and bass response is improved.

2. (currently amended): The loudspeaker ~~according to~~ of claim 1, wherein the generally arcuate source of wind comprises a plurality of electrodynamic loudspeakers disposed in an arcuate line array.

3. (currently amended): The loudspeaker ~~according to~~ of claim 1, comprising a central baffle aligned parallel with a plane defined by the generally arcuate source of wind.

4. (currently amended): The loudspeaker of claim 3, wherein the generally arcuate source of wind comprises a plurality of electrodynamic loudspeakers disposed in at least a portion of a generally arcuate line array, and the loudspeakers are mounted in the surface of the central baffle,
~~and the individual speakers are tilted inward;~~

5. (canceled)

6. (currently amended): The loudspeaker of claim ~~[[2]]~~ 4, comprising a hollow cabinet in which the loudspeakers are mounted, and wherein the loudspeakers are mounted in holes in the surface of the central baffle, wherein the cabinet is sealed.

7. (canceled)

RECEIVED
CENTRAL FAX CENTER

MAR 15 2007

Ser. No. 10/619,294, First Response

8. (currently amended): The loudspeaker of claim ~~[[3]]~~ 1, ~~wherein the generally arcuate source of wind describes an arc of the radius r from a single center point, and further comprising a mount for mounting at least one symmetry baffle aligned substantially perpendicular to the central baffle; a plane including the arcuate source and its radius, and wherein the arcuate source of wind extends around an arc and meets the symmetry baffle generally perpendicularly;~~

9. (currently amended): The loudspeaker of claim 8, wherein the symmetry baffle is a radial symmetry baffle and a center point of the arc lies adjacent the symmetry baffle.

10.-17. (canceled)

18. (previously presented): A method of creating sound of a frequency f , having a wave number k ; the method comprising:

providing a generally arcuate source of pulsating wind having an outer arcuate radius r such that a quantity rk is approximately equal to or larger than one; and

pulsating the wind at the frequency f , whereby the pulsating wind is converted into sound at the frequency f with a high radiation efficiency; ~~[[.]]~~

wherein r is greater than 1.00 feet.

19. (previously presented): The method of claim 18, comprising providing a central baffle aligned with a plane defined by the generally arcuate source of wind.

20. (previously presented): The method of claim 19, comprising providing at least one symmetry baffle aligned substantially perpendicular to the central baffle, and wherein the step of providing a generally arcuate source of pulsating wind includes providing the arcuate source around an arc to meet the symmetry baffle generally perpendicularly.

21. (currently amended): The loudspeaker of claim 4, wherein the speakers are ~~[[all]]~~ tilted relative to the central baffle, at a same angle:

Ser. No. 10/619,294, First Response

22. (new): The loudspeaker of claim 8, wherein the center point is on a central baffle or at an edge of the central baffle.
23. (new): The loudspeaker of claim 1, wherein the arc of the radius r includes a $1/n$ fraction of a whole circle, where n is an integer.
24. (new): The loudspeaker of claim 1, wherein the arc extends around a full circle and the loudspeaker includes a central baffle but lacks a symmetry baffle.
25. (new): The loudspeaker of claim 8, comprising a first symmetry baffle and a second symmetry baffle, and wherein the first symmetry baffle and the second symmetry baffle are set at an angle to one another.
26. (new): A loudspeaker for outputting sound in a frequency range including a lowest frequency f , the lowest frequency f having a wave number k ; the loudspeaker comprising:
a central baffle including a source of wind pulsating at the frequency f , the source extending over an arc of radius r such that a quantity rk is approximately equal to or larger than one;
the central baffle being bounded by at least one symmetry baffle, the symmetry baffle being perpendicular to the central baffle; and
the source of wind being adjacent to the symmetry baffle;
whereby wind is converted into sound at the lowest frequency f and bass response is improved.
27. (new): The loudspeaker of claim 26, wherein r is greater than 1.00 feet.
28. (currently amended): The loudspeaker of claim 21, wherein the speakers are all tilted at a same angle.